

S24885 REV: 4-7-2020 **2021 MODEL YEAR**

92827-92841

TTT **SPECIFICATIONS**

GENERAL

1. TYPE STAINLESS STEEL SEMITRAILER

2. BARREL SHAPE STRAIGHT CYLINDRICAL

3. CODE 3-A SANITARY

4. MAX. PRODUCT DENSITY 9.0 LBS./U.S. GALLON 5. OPERATING PRESSURE **ATMOSPHERIC**

200 F 6. MAX. LOADING TEMP.

7. PRODUCT COMPATIBLE WITH MATERIALS AND DESIGN OF TANK

FHWA INSPECTIONS REQUIRED BY 49 CFR 396.17 PERFORMED BY 8. INSPECTIONS

FACTORY AND LABEL INSTALLED

9. WARRANTY STANDARD THREE YEAR

TTT-91236-91240 10. REFERENCE TRAILER

Section (A) - BARREL

1. CAPACITY 6250 U.S. GALLONS

2. COMPARTMENTS (1) ONE

3. SHELL MATERIAL 12 GAUGE 304 STAINLESS STEEL 4. HEAD MATERIAL 12 GAUGE 304 STAINLESS STEEL 5. INNER SHELL FINISH #4 FINISH, RA OF 32 OR LESS 6. INNER WELD FINISH W5 WELD FINISH, RA OF 32 OR LESS

7. HEAT SYSTEM

8. MANHOLE (1) ONE WALKER 19" S.S. SANITARY WITH S.S. DUST COVER WITH 4 HOLD-

DOWNS AND EPDM GASKET, SEAL TAB PROVISIONS INCLUDED

ALUMINUM, TENSION FIT 9. REINFORCING RINGS

10. CRADLE & FRAME **ALUMINUM**

11. INSULATION 4" URETHANE (225 INSULATION RATING)

12. JACKETING 22 GAUGE BRIGHT ANNEALED STAINLESS STEEL

13. OUTER HEADS 18 GAUGE BLOWN HEADS #3 FINISH

14. EXTENDED FRAME NONE

15. OUTLET 3" POD STYLE OUTLET

Section (B) - KINGPIN

1. KING PIN PLATE BOLTED WITH 2" INCREMENTS. INSTALL STAINLESS STEEL APPROACH

PLATE (#FRM0001760) AND SPACER (#FWP0000069) - LEAVE ONE HOLE

OPEN TO FRONT.

Section (C) - RUNNING GEAR

1. SUSPENSION HENDRICKSON INTRAAX MODEL AANT WITH INTERGRAL AXLE, 71.5" TRACK

WITH TP TYPE SPINDLE, 23,000 LB, BEAM AND BEARING RATING. EQUIPPED WITH 30/30 SPRING BRAKE CHAMBERS, AUTOMATIC SLACK

ADJUSTERS.

AUTOMATIC GLADHAND DUMP 2. DUMP VALVE 3. AXLES AXLE INCLUDED WITH INTRAAX

4. LIFT AXLE NONE 5. SPREAD AXLE NONE

HXS EXTENDED LIFE, 16.5" X 7", NON-ASBESTOS 6. BRAKES

7. SUSPENSION FRAME ALUMINUM

8. ABS MERITOR WABCO 4S-2M ABS WITH ROLL STABILITY SYSTEM

8/26/2020 1

| Customer A | Approval | : | |
|------------|----------|---|--|
| | • • | | |

(9. HUBS WALTHER EMC DURALITE TP 10 STUD, HUB PILOTED. USE STUDS LONG

ENOUGH FOR ALUMINUM WHEELS. HUBS FILLED WITH SAE 80W90 GEAR

OIL

10. DRUMS 16.5" X 7" CAST BRAKE DRUMS

X 11. BUMPER NONE

X 12. REAR UNDER-RIDE REAR UNDER-RIDE MEETING NHTSA AND DOT REQUIREMENTS - WITH

STAINLESS STEEL END PLUGS

13. TIRE INFLATION NONE

Section (D) - TIRES/WHEELS

(1. TIRES CUSTOMER SUPPLIED GOODYEAR TIRES

X 2. WHEELS CUSTOMER SUPPLIED 8.25 X 22.5 FOR 10 HOLE HUBS, ALUMINUM MILL

FINISH, HUB PILOTED

3. BRANDING NONE

Section (E) - LANDING GEAR

X 1. LANDING GEAR JOST 2-SPEED LANDING GEAR WITH EXTRA FRONT CROSSBRACE

2. CRANK LOCATION CURBSIDE CRANK

🕻 3. TIRE CARRIER BASKET TYPE AT LANDING GEAR AREA

Section (F) - LADDER/WALKWAY

1. LADDER (2) STAINLESS STEEL WITH PLATFORM TOP STEP AND DIMPLED CHANNEL

RUNGS (LOCATED ONE EACH SIDE)

2. DUAL SAFETY HAND RAILS NONE

3. WALKWAY 23.5" X 30" ALUMINUM SAFETY GRATING AT REAR OF MANHOLE

4. SPILLDAM SQUARE DESIGN, 30" X 30" NON-CODE WITH DRAINS INCORPORATED IN

LADDER RAILS

Section (G) - CABINET

1. UTILITY CABINET NONE
2. CABINET DOOR SUPPORTS NONE
3. DIRECT SHIP SHROUD NONE

Section (H) - HYDRAULICS

1. HYDRAULIC LINES NONE
2. LOCATION NONE
3. HYDRAULIC FITTINGS NONE

Section (I) - VALVING/PIPING

1. OUTLET VALVE 3" 60TTF VALVE WITH ALUMINUM DUST HOOD

2. OUTLET FITTINGS NONE

Section (J) - VENTING

1. PRESSURE RELIEF VENTING (1) 3" OLSON SPRING LOADED VENT IN MANHOLE COVER

2. VACUUM VENTING INCLUDED IN OLSON VENT

3. VENT PROTECTION NONE

Section (K) - HOSE CARRIER

1. HOSE CARRIER NONE
2. HOSE CARRIER LOCATIONS NONE
3. HOSE CARRIER ACCESSORIES NONE

Section (L) - WIRING

1. NOSE BOX GROTE ATA 7-WAY WITHOUT CIRCUIT BREAKERS, LOCATED BELOW

CENTERLINE, DRIVERSIDE OF FRONT HEAD. BLUE WIRED TO ABS SYSTEM.

X 2. LIGHTS GROTE HARNESS SYSTEM WITH 7 YEAR WARRANTY AND WITHOUT

JUNCTION BOX AND GROTE LED LIGHTS WITH 10 YEAR WARRANTY AND MALE PINS. SIDE CENTER MARKER LIGHTS WIRED TO FLASH WITH TURN

SIGNALS.

3. LIGHT BOXES STEEL, BOLTED ON

8/26/2020 Customer Approval:____

4. WIDE TURN LIGHTS NONE

Section (M) - FENDER

1. FENDERS ALUMINUM FENDERS AT FRONT AND REAR WITH ALUMINUM SUPPORT AND

STAINLESS STEEL HARDWARE, FRONT FENDER SUPPORTS LOCATED

UNDER FENDERS. FRONT FENDERS CAPPED.

Section (N) - PAINT/DECAL

1. PAINT CARBON STEEL PARTS PRIMED AND PAINTED BLACK

2. CONSPICUITY REFLECTIVE STRIPING ON EACH SIDE AND REAR OF TRAILER

3. DECALS NO CUSTOMER SPECIFIC DECALS

Section (O) - MISC

1. CALIBRATION THEORETICAL ON REQUEST

2. CAPACITY INDICATOR NONE
3. PASSIVATION NONE

4. MUDFLAPS (2) PAIR OF ANTISAIL

5. HUBODOMETER NONE
6. THERMOMETER NONE

7. GASKETS GASKET WITH SEAL TAB PROVISIONS INCLUDED
8. SEALS-PROVISIONS GOVERNMENT SEAL CAPABILITY ON ALL OPENINGS

9. C.I.P. PROVISION NONE
10. C.I.P. ACCESSORIES NONE
11. DUST COVER NONE
12. PLACARD HOLDERS NONE

13. REGISTRATION HOLDER (1) REGISTRATION HOLDER MOUNTED DRIVERSIDE IN LANDING GEAR

14. CUSTOMER SPECIFIC TRACTOR DATA NONE
15. CUSTOMER SPECIFIC TRAILER LENGTH NONE
16. CUSTOMER SPECIFIC TANDEM SETTING NONE

ORIGINALLY STATED:

| Sec | tion (B) - KINGPIN | |
|-----|--------------------|--|
| X | 1. KING PIN PLATE | BOLTED WITH 2" INCREMENTS. INSTALL STAINLESS STEEL APPROACH PLATE (#FRM0001760) AND SPACER (#FWP0000069) |

Customer Approval:_____

8/26/2020 3